



SAFETY DATA SHEET

Revision Date 25-Jan-2017

Version 2

1. IDENTIFICATION

Product identifier

Product Name Wynn's Stop Squeak

Other means of identification

Product Code WN 63501

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Uses advised against All other applications

Details of the supplier of the safety data sheet

Supplier Address

ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Manufacturer Address

May Also Be Distributed by:

ITW Professional Automotive Products
1-35 Brownridge Road
Halton Hills, ON, Canada L7G 0C6

Manufactured and Distributed by:

ITW Professional Automotive Products
3606 Craftsman Blvd
Lakeland, FL 33803

Distributor

Company Phone Number 863-665-3338

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

E-mail address EHS@itwproap.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Emergency Overview

Danger

Causes serious eye irritation
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor

**Appearance** Black**Physical state** Liquid**Odor** Alcohol**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Wear protective gloves/protective clothing/eye protection/face protection
 Keep cool

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- May be harmful in contact with skin
- Causes mild skin irritation

Unknown acute toxicity

20 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%	Trade Secret
Isopropanol	67-63-0	60 - 100	*
Graphite	7782-42-5	10 - 30	*
n-Butyl alcohol	71-36-3	1 - 5	*
1-Methoxy -2-propanol	107-98-2	1 - 5	*

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None.

Specific hazards arising from the chemical

Flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Use personal protective equipment as required.

Environmental precautions

Environmental precautions See Section 12 for additional ecological information. Do not flush into surface water or sanitary sewer system.

Methods and material for containment and cleaning up

Methods for containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Soak up with inert absorbent material.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.
--------------------------------	--

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).
Incompatible materials	Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ natural respirable dust
n-Butyl alcohol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
1-Methoxy -2-propanol 107-98-2	STEL: 100 ppm TWA: 50 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m ³	TWA: 100 ppm TWA: 360 mg/m ³ STEL: 150 ppm STEL: 540 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).
--------------------------	---

Appropriate engineering controls

Engineering Controls	Showers Eyewash stations Ventilation systems
-----------------------------	--

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Physical state	Liquid
Appearance	Black
Odor	Alcohol
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available 82 °C / 180 °F	
Flash point	12 °C / 54 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.89	
Water solubility	Dispersible	
Solubility in other solvents	No information available	
Partition coefficient	-0.14	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	19 mm ² /s	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	No information available
Bulk density	No information available

10. STABILITY AND REACTIVITY**Reactivity**

No data available

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Excessive heat.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Isopropanol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m ³ (Rat) 4 h
n-Butyl alcohol 71-36-3	= 700 mg/kg (Rat) = 790 mg/kg (Rat)	= 3402 mg/kg (Rabbit) = 3400 mg/kg (Rabbit)	> 8000 ppm (Rat) 4 h
1-Methoxy -2-propanol 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0	-	Group 3	-	X

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	28070 mg/kg
ATEmix (dermal)	4039 mg/kg
ATEmix (inhalation-dust/mist)	61.1 mg/l
ATEmix (inhalation-vapor)	492800 mg/l

12. ECOLOGICAL INFORMATION**Ecotoxicity**

20 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
Isopropanol 67-63-0	0.05
n-Butyl alcohol 71-36-3	0.785
1-Methoxy -2-propanol 107-98-2	-0.437

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

- Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).
- Contaminated packaging** Do not reuse container.
- US EPA Waste Number** D001, U031

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Isopropanol 67-63-0	Toxic Ignitable
n-Butyl alcohol 71-36-3	Toxic

14. TRANSPORT INFORMATION

DOT

- UN/ID no** UN1993
Proper shipping name: Flammable liquids, n.o.s, (contains isopropanol), Limited Quantity (LQ)
Packing Group II

IATA

- UN/ID no** UN1993
Proper shipping name: Flammable liquid, n.o.s, (contains isopropanol), Limited Quantity (LQ)
Packing Group II

IMDG

- UN/ID no** UN1993
Proper shipping name: Flammable liquids, n.o.s, (contains isopropanol), Limited Quantity (LQ)
Packing Group II

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS - Japan Existing and New Chemical Substances
- IECSC - China Inventory of Existing Chemical Substances
- KECL - Korean Existing and Evaluated Chemical Substances
- PICCS - Philippines Inventory of Chemicals and Chemical Substances
- AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	1.0
n-Butyl alcohol - 71-36-3	1.0

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
n-Butyl alcohol 71-36-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Isopropanol 67-63-0	X	X	X
Graphite 7782-42-5	X	X	X
n-Butyl alcohol 71-36-3	X	X	X
1-Methoxy -2-propanol 107-98-2	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

D2A - Very toxic materials, B2 - Flammable liquid

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Flammability 3	Instability 0	-	HMIS
Flammability 3	Physical hazards 0	Personal protection B		

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Revision Date 25-Jan-2017

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet