



# TRANSMISSION

## AUTOMATIC TRANSMISSION FLUID (ATF)

### APPLICATION CHART

Technical Services: 800-255-8138, Option 4

OEM	Specification	Viscosity	Suitable for Use	Component Type
Aisin Warner	Aisin AW-1, JWS 3309	High	YES	Automatic Transmission
	JWS 3324	Low	YES	Automatic Transmission
Allison	C-4, TES-295, TES-389, TES-389B	High	YES	Automatic Transmission
Audi/VW	TL 052 162 (Reference spec ESSO LT 71141), TL 052 990, TL 055 025-A	High	YES	Automatic Transmission
	Porsche 000.043.204.63, Porsche 000.043.205.28	High	YES	Automatic Transmission
	TL 052 162-X, TL 052 162-Y, TL 052 162-Z, TL 052 540-B	Low	YES	Automatic Transmission
BMW	BMW 83 22 2 152 426, BMW 83 22 2 305 397 (ATF 3), BMW 83 22 0 142 516, BMW 83 22 2 289 720 (ATF3+), BMW 83 22 0 397 114	Low	YES	Automatic Transmission
	BMW 83 22 0 026 922, BMW 83 22 9 407 807	High	YES	Automatic Transmission
BMW MINI	BMW 83 22 7 542 290	High	YES	Automatic Transmission
Daihatsu*	Ammix D-III ATF	High	YES	Automatic Transmission
DSIH**	6p805	Low	YES	Automatic Transmission
Fiat Chrysler Automobiles	ZF 8 and 9 speed (color does not match), Mopar DEX-VI, Mopar SP-IV ATF, SP-IV-M	Low	YES	Automatic Transmission
	ATF+4, ATF+3, ATF+2, MOPAR AS68/69RC	High	YES	Automatic Transmission
	Chrysler MS-1872, Chrysler MS-5931, Chrysler MS-10838	High	YES	Power Steering
Ford	Mercon®LV, SP	Low	YES	Automatic Transmission
	Mercon®V	High	YES	Automatic Transmission
	Ford M	High	YES	Automatic Transmission & Transfer Case
	Ford FNR5, WSS-M2C922, WSS-M2C924-A	High	YES	Automatic Transmission
	WSS-M2C138, WSS-M2C195-A	High	YES	Power Steering
	Ford XL-12	High	YES	Transfer Case

\*Daihatsu Ammix D-III: Daihatsu only; \*\*DSIH ATF: Australian, Chinese and European Car and Truck 6-Speed Transmission

#### Applicable to the Following Wynn's Products:

Low Viscosity ATF	High Viscosity ATF	Net Fill	Quantity Per Case
ZWA5301	ZWA5401	32 OZ (946 mL)	12
ZWA5302	ZWA5402	54 GAL (204 L)	1
ZWA5303	ZWA5403	1 GAL (3.78 L)	4

**NOTE:** This chart contains the latest information available to ITW ProAP and is believed to be current and accurate. ITW ProAP is not responsible for any errors or omissions by original manufacturers.



# TRANSMISSION

## AUTOMATIC TRANSMISSION FLUID (ATF)

### APPLICATION CHART

Technical Services: 800-255-8138, Option 4

OEM	Specification	Viscosity	Suitable for Use	Component Type
GM	AW-1 Transmission Fluid, T-IV Transmission Fluid, T-VI Transmission Fluid, ATF Saturn T-IV, DEX	High	YES	Automatic Transmission
	GM WS-ATF (Reference spec JWS 3324), Dexron®VI	Low	YES	Automatic Transmission
	TASA*	High	YES	Automatic Transmission
	GM Auto Trak II	High	YES	Transfer Case
	GM Dexron®IID, GM Dexron®IIIF, GM Dexron®IIIG, GM Dexron®IIIH, GM Dexron®III	High	YES	Automatic Transmission; Transfer Case
	Dexron®HP	NA	NO	NA
	Power Steering Fluid, 9985010, 9985835	High	YES	Power Steering
Honda	Honda Type 3.0, Honda ATF DW-1	Low	YES	Automatic Transmission
	Honda ATF-Z1	High	YES	Automatic Transmission
Hyundai/Kia	Hyundai SP-IV, Hyundai SP-IV-RR, Hyundai NWS 9638, Hyundai SP-IV M, Hyundai SPH-IV	Low	YES	Automatic Transmission
	Kia Red-1, JWS 3314, JWS 3317, Hyundai SP, Hyundai SP-II, Hyundai SP-III	High	YES	Automatic Transmission
	PSF-3	High	YES	Power Steering
Isuzu	Isuzu SCS	Low	YES	Automatic Transmission
Jaguar	Jaguar Fluid 8432, Jaguar Fluid JDE26444	Low	YES	Automatic Transmission
JASO	JASO 1-A	High	YES	Automatic Transmission
	JASO 1-A-LV	Low	YES	Automatic Transmission
Jatco	Nissan 402, Texaco 402, 3100 PL085	High	YES	Automatic Transmission
Land Rover	Synthetic Dexron 3, Texaco N402, LRN402, ESSO LT71141, STC 4863 (aligns with ZF S671 090 170), Esso JWS3309 US	High	YES	Automatic Transmission
	TYK50050, Shell M1375.4, ATF L12108, Nippon AW-1 ATF	Low	YES	Automatic Transmission
	See ZF for more specs	See ZF	See ZF	See ZF
MAN**	MAN 339 V-1, MAN 339 Z-1, MAN 339F	High	YES	Automatic Transmission

\*GM TASA: HD Trucks \*\*MAN : HD Import

#### Applicable to the Following Wynn's Products:

Low Viscosity ATF	High Viscosity ATF	Net Fill	Quantity Per Case
ZWA5301	ZWA5401	32 OZ (946 mL)	12
ZWA5302	ZWA5402	54 GAL (204 L)	1
ZWA5303	ZWA5403	1 GAL (3.78 L)	4

**NOTE:** This chart contains the latest information available to ITW ProAP and is believed to be current and accurate. ITW ProAP is not responsible for any errors or omissions by original manufacturers.



# TRANSMISSION

## AUTOMATIC TRANSMISSION FLUID (ATF)

### APPLICATION CHART

Technical Services: 800-255-8138, Option 4

OEM	Specification	Viscosity	Suitable for Use	Component Type
Mazda	Mazda M-III	High	YES	Automatic Transmission & Power Steering
	Mazda M-V	High	YES	Automatic Transmission
	Mazda ZF	NA	NO	NA
Mercedes	MB 236.6, MB 236.10, MB 236.1, MB 236.2, MB 236.5, MB 236.7, MB 236.9, MB 236.81, MB 236.91, MB 236.11	High	YES	Automatic Transmission
	MB 236.3	High	YES	Power Steering
	MB 236.12, MB 236.14, MB 236.15, MB 236.16, MB 236.17	Low	YES	Automatic Transmission
	Mercedes GL-450	High	YES	Transfer Case
Mitsubishi	Mitsubishi SP-II, Mitsubishi SP-III, Mitsubishi Dia Queen ATF J2	High	YES	Automatic Transmission
	Mitsubishi Dia Queen ATF J3, Mitsubishi Dia Queen ATF-PA	Low	YES	Automatic Transmission
	Mitsubishi PS Fluid, Mitsubishi Diamond SP-III	High	YES	Power Steering
Nissan	Nissan Matic D, Nissan Matic J, Nissan Matic K, Nissan Matic C	High	YES	Automatic Transmission
	Nissan Matic S	Low	YES	Automatic Transmission
	Nissan Matic W	Low	YES	eCVT
	Nissan PSF-II	High	YES	Power Steering
PSA*	B71 2340	High	YES	Automatic Transmission
Renault**	DP-0	High	YES	Automatic Transmission
Saab	Saab 93165147	High	YES	Automatic Transmission
	Saab Power Steering Fluid 2634	High	YES	Power Steering

\*PSA: Peugeot/Citroën; \*\*Renault: DP-0 FWD 4 Speed Electronic also used in Citroën & Peugeot;

#### Applicable to the Following Wynn's Products:

Low Viscosity ATF	High Viscosity ATF	Net Fill	Quantity Per Case
ZWA5301	ZWA5401	32 OZ (946 mL)	12
ZWA5302	ZWA5402	54 GAL (204 L)	1
ZWA5303	ZWA5403	1 GAL (3.78 L)	4

**NOTE:** This chart contains the latest information available to ITW ProAP and is believed to be current and accurate. ITW ProAP is not responsible for any errors or omissions by original manufacturers.



# TRANSMISSION

## AUTOMATIC TRANSMISSION FLUID (ATF)

### APPLICATION CHART

Technical Services: 800-255-8138, Option 4

OEM	Specification	Viscosity	Suitable for Use	Component Type
Subaru	Subaru ATF, Subaru ATF HP	High	YES	Automatic Transmission
	Power Steering Fluid	High	YES	Power Steering
Suzuki	Suzuki 3314, Suzuki 3317	High	YES	Automatic Transmission
Toyota	Toyota T-IV, Toyota T, Toyota T-I, Toyota T-II, Toyota T-III	High	YES	Automatic Transmission
	Toyota WS	Low	YES	Automatic Transmission
	Toyota PSF Type EH	High	YES	Power Steering
Voith	Voith H55.6335	High	YES	Automatic Transmission
Volvo	Volvo 1161621, Volvo 1161521, Volvo 1161640, Volvo 1161540, Volvo 97341, Volvo 97340, Volvo 31256774	High	YES	Automatic Transmission
ZF	ZF LifeGuardFluid5, ZF TE-ML 21L, ZF TE-ML 11 (3, 4 and 5 speeds), ZF TE-ML 04D, ZF TE-ML 05L, ZF TE-ML 17C, ZF TE-ML 16L, ZF TE-ML 14A, ZF TE-ML 03D	High	YES	Automatic Transmission
	ZF TE-ML 09	High	YES	Automatic Transmission & Power Steering
	ZF LifeGuardFluid6, ZF LifeGuardFluid6+, ZF TE-ML 11 (6 speeds), ZF TE-ML 11 (8, 9 speeds)	Low	YES	Automatic Transmission

#### Applicable to the Following Wynn's Products:

Low Viscosity ATF	High Viscosity ATF	Net Fill	Quantity Per Case
ZWA5301	ZWA5401	32 OZ (946 mL)	12
ZWA5302	ZWA5402	54 GAL (204 L)	1
ZWA5303	ZWA5403	1 GAL (3.78 L)	4

**NOTE:** This chart contains the latest information available to ITW ProAP and is believed to be current and accurate. ITW ProAP is not responsible for any errors or omissions by original manufacturers.