SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 16-Mar-2026 **Version** 3

1. Identification

Product identifier

Product Name Wynn's Diesel Injector Purge

Other means of identification

Product Code WN 15402

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address
ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Manufacturer Address

Manufactured and Distributed by:

Distributor

May Also Be Distributed by:
Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

E-mail address EHS@itwproap.com

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Flammable liquids	Category 3
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 1B
Aspiration hazard	Category 1

Label elements

Danger

Hazard statements
Flammable liquid and vapor.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause cancer.
May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Wash face, hands and any exposed skin thoroughly after handling.
Avoid breathing dust, fume, gas, mist, vapors and spray.
Contaminated work clothing must not be allowed out of the workplace.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Use explosion-proof electrical, ventilating and lighting equipment.
Precautionary Statements - Response
IF exposed or concerned: Get medical advice and attention.
Specific treatment (see supplemental first aid instructions on this label).
Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice and attention.
Skin
IF ON SKIN: Wash with plenty of water and soap.
If skin irritation or rash occurs: Get medical advice and attention.
Take off contaminated clothing and wash it before reuse.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Do NOT induce vomiting.
Fire
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage
Store locked up.
Store in a well-ventilated place. Keep cool.
Precautionary Statements - Disposal
Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

58.56 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
28.4964 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
97.1564 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

Hazards classified under paragraph (d)(1)(ii) of 1910.1200
No information available.

Other Information
May be harmful if swallowed. May be harmful in contact with skin. Causes mild skin irritation. Toxic to aquatic life with long lasting

effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Fuels, diesel, no. 2	68476-34-6	15-40%	-	-
4-methylpentan-2-ol	108-11-2	1-5%	-	-
Naphtha (petroleum), heavy aromatic	64742-94-5	1-5%	-	-
Naphthalene	91-20-3	1-5%	-	-
2-ETHYL-1-HEXANOL	104-76-7	0.5-1.5%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice and attention. Immediate medical attention is required.

Inhalation Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.

Ingestion ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. Do NOT induce vomiting. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes. Burning sensation. Prolonged contact may cause redness and irritation.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically. Because of the danger of aspiration, emesis or gastric lavage should not be employed unless the risk is justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protective equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Fuels, diesel, no. 2 68476-34-6	TWA: 100 mg/m³ total Hydrocarbons inhalable fraction and vapor pSk	-	-
4-methylpentan-2-ol 108-11-2	TWA: 20 ppm STEL: 40 ppm	TWA: 25 ppm TWA: 100 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 100 mg/m³ (vacated) STEL: 40 ppm (vacated) STEL: 165 mg/m³ dSk Sdv	TWA: 25 ppm; TWA: 100 mg/m³; STEL: 40 ppm STEL: 165 mg/m³ IDLH: 400 ppm
Naphthalene 91-20-3	TWA: 10 ppm pSk	TWA: 10 ppm TWA: 50 mg/m³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m³	TWA: 10 ppm; TWA: 50 mg/m³; STEL: 15 ppm STEL: 75 mg/m³ IDLH: 250 ppm
2-ETHYL-1-HEXANOL 104-76-7	TWA: 5 ppm	-	-

Chemical name	Alberta	British Columbia	Ontario	Quebec
Fuels, diesel, no. 2 68476-34-6	TWA: 100 mg/m³;	TWA: 100 mg/m³; inhalable; inhalable aerosol and vapour Sk	TWA: 100 mg/m³; inhalable fraction and vapor dSk	TWAEV: 100 mg/m³; inhalable fraction and vapour Sd
4-methylpentan-2-ol 108-11-2	TWA: 25 ppm; TWA: 104 mg/m³; STEL: 40 ppm; STEL: 167 mg/m³; pSk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; dSk	TWAEV: 20 ppm; STEV: 40 ppm;
Naphthalene 91-20-3	TWA: 10 ppm; TWA: 52 mg/m³;	TWA: 10 ppm; Sk	TWA: 10 ppm; dSk	TWAEV: 10 ppm; Sd

	STEL: 15 ppm; STEL: 79 mg/m³; pSk			

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Fuels, diesel, no. 2	TWA: 100 mg/m³; inhalable fraction and vapor pSk	TWA: 100 mg/m³; inhalable fraction and vapor pSk	TWA: 100 mg/m³; inhalable fraction and vapor pSk	TWA: 100 mg/m³; inhalable fraction and vapor pSk
4-methylpentan-2-ol	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; pSk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 20 ppm; STEL: 40 ppm;
Naphthalene	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk	TWA: 10 ppm; pSk
2-ETHYL-1-HEXANOL	TWA: 5 ppm;		TWA: 5 ppm;	TWA: 5 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Fuels, diesel, no. 2	TWA: 100 mg/m³; vapour STEL: 150 mg/m³; vapour Sk	TWA: 100 mg/m³; inhalable fraction and vapor	TWA: 100 mg/m³; vapour STEL: 150 mg/m³; vapour pSd	
4-methylpentan-2-ol	TWA: 25 ppm; STEL: 40 ppm; Sk	TWA: 20 ppm; STEL: 40 ppm;	TWA: 25 ppm; STEL: 40 ppm; pSd	TWA: 25 ppm; TWA: 100 mg/m³; STEL: 40 ppm; STEL: 150 mg/m³; Sk
Naphthalene	TWA: 10 ppm; STEL: 15 ppm; Sk	TWA: 10 ppm;	TWA: 10 ppm; STEL: 15 ppm; pSd	TWA: 10 ppm; TWA: 50 mg/m³; STEL: 15 ppm; STEL: 75 mg/m³;
2-ETHYL-1-HEXANOL		TWA: 5 ppm;		

Biological occupational exposure limits

Chemical name	ACGIH
Naphthalene 91-20-3	- (1-Naphthol with hydrolysis plus 2-Naphthol with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire

resistant or flame retardant clothing.

Respiratory protection Use appropriate respiratory protection. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear protective gloves, eye protection and face protection.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Clear
Physical state	Liquid
Color	Amber
Odor (includes odor threshold)	

Property	**Values**	**Remarks • Method**
Melting point / freezing point	No data available	
Boiling point (or initial boiling point or boiling range)	> 35 °C / 95 °F	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	No data available	
Lower flammability limit:	No data available	
Flash point	57 °C / 134.6 °F	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
SADT (°C)	No data available	
pH	No data available	
pH (as aqueous solution)	No data available	
Kinematic viscosity	2 mm²/s	
Dynamic viscosity	No data available	
Solubility	No Data Available	
Water solubility	Insoluble in water	
Partition coefficient n-octanol/water (log value)	No Data Available	
Vapor pressure (includes evaporation rate)	No Data Available	
Evaporation rate	Not applicable	
Density and/or relative density	0.88	
Bulk density	No data available	
Density	No data available	
Vapor density	No data available	
Particle characteristics		
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

VOC content	10.269

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness or cracking. Prolonged contact may cause redness and irritation. Causes mild skin irritation. May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May cause redness and tearing of the eyes.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	3,612.70 mg/kg
ATEmix (dermal)	2,044.90 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	24.80 mg/L
ATEmix (inhalation-dust/mist)	99,999.00 mg/L

58.56 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
28.4964 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
97.1564 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Fuels, diesel, no. 2 68476-34-6	-	> 2000 mg/kg (Rabbit)	= 3.6 mg/L (Rat) 4 h = 5.4 mg/L (Rat) 4 h
4-methylpentan-2-ol	= 2600 mg/kg (Rat)	= 2880 mg/kg (Rabbit)	> 16000 mg/m³ (Rat) 4 h

108-11-2			
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 590 mg/m³ (Rat) 4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat)	= 1120 mg/kg (Rabbit)	> 0.4 mg/L (Rat) 4 h
2-ETHYL-1-HEXANOL 104-76-7	= 3730 mg/kg (Rat)	= 1980 mg/kg (Rabbit)	> 227 ppm (Rat) 6 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Fuels, diesel, no. 2 68476-34-6	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-
Naphthalene 91-20-3	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present
2-ETHYL-1-HEXANOL 104-76-7	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	-	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
NTP (National Toxicology Program)
Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
Occupational Safety and Health Administration of the US Department of Labor
X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Fuels, diesel, no. 2 68476-34-6	-	LC50: =35mg/L (96h, Pimephales promelas)	-	-
4-methylpentan-2-ol 108-11-2	-	LC50: >92.4mg/L (96h, Pimephales promelas)	-	-
Naphtha (petroleum), heavy aromatic 64742-94-5	-	LC50: =19mg/L (96h, Pimephales promelas) LC50: =2.34mg/L (96h, Oncorhynchus mykiss) LC50: =1740mg/L (96h, Lepomis macrochirus) LC50: =45mg/L (96h, Pimephales promelas) LC50: =41mg/L (96h, Pimephales promelas)	-	EC50: =0.95mg/L (48h, Daphnia magna)
Naphthalene 91-20-3	-	LC50: 5.74 - 6.44mg/L (96h, Pimephales promelas) LC50: =1.6mg/L (96h, Oncorhynchus mykiss) LC50: 0.91 - 2.82mg/L (96h, Oncorhynchus mykiss) LC50: =1.99mg/L (96h, Pimephales promelas) LC50: =31.0265mg/L (96h, Lepomis macrochirus)	-	LC50: =2.16mg/L (48h, Daphnia magna) EC50: =1.96mg/L (48h, Daphnia magna) EC50: 1.09 - 3.4mg/L (48h, Daphnia magna)
2-ETHYL-1-HEXANOL 104-76-7	EC50: =11.5mg/L (72h, Desmodesmus subspicatus)	LC50: 32 - 37mg/L (96h, Oncorhynchus mykiss) LC50: >7.5mg/L (96h, Oncorhynchus mykiss) LC50: 27 - 29.5mg/L (96h, Pimephales promelas) LC50: =29.7mg/L (96h, Pimephales promelas) LC50: 10.0 - 33.0mg/L (96h, Lepomis macrochirus)	-	EC50: =39mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulative potential

Component Information

Chemical name	Partition coefficient
4-methylpentan-2-ol 108-11-2	1.43
Naphtha (petroleum), heavy aromatic 64742-94-5	6.5
Naphthalene 91-20-3	3.4

2-ETHYL-1-HEXANOL 104-76-7	2.9

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number D001, U165 U239

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

Note: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN number or ID number UN1993
Proper shipping name Flammable liquids, n.o.s. (contains Diesel Fuel) Limited Quantity (LQ)
Transport hazard class(es) 3
Packing group III

IATA

UN number or ID number UN1993
UN proper shipping name Flammable liquids, n.o.s. (contains Diesel Fuel) Limited Quantity (LQ)
Transport hazard class(es) 3
Packing group III

IMDG

UN number or ID number UN1993
UN proper shipping name Flammable liquids, n.o.s. (contains Diesel Fuel) Limited Quantity (LQ)
Transport hazard class(es) 3
Packing group III

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Naphthalene - 91-20-3	0.1

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthalene 91-20-3	100 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Naphthalene 91-20-3	100 lb / 1 lb / kg (final RQ)	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ

	kg (final RQ)		RQ 0.454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental
BENZENE - 71-43-2	Carcinogen Developmental Male Reproductive

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Kerosene (petroleum) 8008-20-6	X	X	X
4-methylpentan-2-ol 108-11-2	X	X	X
Naphthalene 91-20-3	X	X	X
2-ETHYL-1-HEXANOL 104-76-7	-	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X
Tetraethylenepentamine 112-57-2	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
Diisobutylketone 108-83-8	X	X	X
BENZENE 71-43-2	X	X	X

16. Other information

NFPA **Health hazards** 2 **Flammability** 2 **Instability** 0 **Special hazards** -

HMIS **Health hazards** 2* **Flammability** 2 **Physical hazards** 0 **Personal protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Revision Date 16-Mar-2026

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However,Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.