SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 18-Aug-2025 **Version** 1

1. Identification

Product identifier

Product Name Wynn's Evaporator & Heater Core Cleaner

Other means of identification

Product Code WN 63701

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on use All other applications

Details of the supplier of the safety data sheet

Supplier Address
ITW Professional Automotive Products
3606 Craftsman Blvd.
Lakeland, FL 33803

Manufacturer Address

Manufactured and Distributed by:

Distributor

May Also Be Distributed by:
Logistic Distribution
550 Industrial Drive
Milton, ON, Canada L9T 5A6

Emergency telephone number

Company Phone Number 863-665-3338

24-hour emergency phone number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003583

2. Hazard(s) identification

Classification of the substance or mixture

Aerosols	Category 2
Skin corrosion/irritation	Category 1
Serious eye damage/eye irritation	Category 1

Label elements

Danger

Hazard statements
Flammable aerosol. Pressurized container: May burst if heated.
Causes severe skin burns and eye damage.

Precautionary Statements - Prevention
Wear protective gloves, protective clothing, eye protection and face protection.
Do not breathe dust.
Wash face, hands and any exposed skin thoroughly after handling.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Do not pierce or burn, even after use.
Do not spray on an open flame or other ignition source.
Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention.
Immediately call a POISON CENTER or doctor.
Specific treatment (see supplemental first aid instructions on this label).
Eyes
Immediately call a POISON CENTER or doctor.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Skin
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
Wash contaminated clothing before reuse.
Inhalation
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor.
Rinse mouth.
Do NOT induce vomiting.

Precautionary Statements - Storage
Store locked up.
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
Precautionary Statements - Disposal
Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

3.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
3.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
3.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

Hazards classified under paragraph (d)(1)(ii) of 1910.1200
No information available.

Other Information
No information available.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Chemical name	CAS No.	Weight-%	**Hazardous Material Information Review Act registry number (HMIRA registry #)**	**Date HMIRA filed and date exemption granted (if applicable)**
Propane	74-98-6	1-5%	-	-
Ethylene Glycol Monobutyl Ether	111-76-2	1-5%	-	-
Tetrasodium ethylenediamine tetraacetate	64-02-8	0.1-1%	-	-
Acetaldehyde	75-07-0	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. Immediate medical attention is required. IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area. Get immediate medical attention.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get immediate medical attention.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Wear personal protective clothing (see section 8). Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors.

Explosion data
Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapors/spray. Attention! Corrosive material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapors or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition (i.e.,

pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Protect from moisture. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Propane 74-98-6	: See Appendix F: Minimal Oxygen Content, explosion hazard Sa	TWA: 1000 ppm TWA: 1800 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m³	TWA: 1000 ppm; TWA: 1800 mg/m³; IDLH: 2100 ppm
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ dSk Sdv	TWA: 5 ppm; TWA: 24 mg/m³; IDLH: 700 ppm
Acetaldehyde 75-07-0	Ceiling: 25 ppm	TWA: 200 ppm TWA: 360 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 180 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 270 mg/m³	IDLH: 2000 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
Propane 74-98-6	TWA: 1000 ppm;	Sa	: ; Sa (See Appendix F: Minimal Oxygen Content;explosion hazard)	Sa
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm; TWA: 97 mg/m³;	TWA: 20 ppm;	TWA: 20 ppm;	TWAEV: 20 ppm;
Acetaldehyde 75-07-0	Ceiling: 25 ppm; Ceiling: 45 mg/m³;	Ceiling: 25 ppm;	Ceiling: 25 ppm;	Ceiling: 25 ppm; Ceiling: 45 mg/m³;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Propane	: ; Sa (See Appendix F: Minimal Oxygen Content)	: ;	: ;	: ; Sa (See Appendix F: Minimal Oxygen Content)
Ethylene Glycol Monobutyl Ether	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;
Acetaldehyde	Ceiling: 25 ppm;	Ceiling: 25 ppm;	Ceiling: 25 ppm;	Ceiling: 25 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Propane	TWA: 1000 ppm; STEL: 1250 ppm;	: ;	TWA: 1000 ppm; STEL: 1250 ppm;	Sa
Ethylene Glycol Monobutyl Ether	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 50 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
	STEL: 30 ppm;		STEL: 30 ppm;	TWA: 240 mg/m³; STEL: 150 ppm; STEL: 720 mg/m³; Sk
Acetaldehyde	Ceiling: 25 ppm; Designated substance	Ceiling: 25 ppm;	Ceiling: 25 ppm; Designated Chemical Substance	TWA: 100 ppm; TWA: 180 mg/m³; STEL: 150 ppm; STEL: 270 mg/m³;

Biological occupational exposure limits

Chemical name	ACGIH
Ethylene Glycol Monobutyl Ether 111-76-2	200 mg/g creatinine - urine (Butoxyacetic acid with hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Face protection shield. Tight sealing safety goggles. Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Chemical resistant apron. Antistatic boots. Wear fire/flame resistant/retardant clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Appearance Foam Liquid
Physical state Aerosol
Color Colorless
Odor (includes odor threshold)

Property	Values	Remarks • Method
Melting point / freezing point	No data available	
Boiling point (or initial boiling point or boiling range)	36 °C / 96.8 °F	
Flammability (solid, gas)	Flammable Aerosol	
Flammability Limit in Air		

Upper flammability limit:	No data available
Lower flammability limit:	No data available
Flash point	Not applicable to aerosols
Autoignition temperature	No data available
Decomposition temperature	No data available
SADT (°C)	No data available
pH	13
pH (as aqueous solution)	No data available
Kinematic viscosity	< 14 mm2/s
Dynamic viscosity	No data available
Solubility	No Data Available
Water solubility	No data available
Partition coefficient n-octanol/water (log value)	No Data Available
Vapor pressure (includes evaporation rate)	50-70
Evaporation rate	Not applicable
Density and/or relative density	1.019
Bulk density	No data available
Density	No data available
Vapor density	No data available
Particle characteristics	
Particle Size	No data available
Particle Size Distribution	No data available

Other information

10. Stability and reactivity

Reactivity Stable under normal conditions.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible materials Acids. Bases. Oxidizing agent.

Hazardous decomposition products Carbon dioxide (CO2). Carbon monoxide.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. Corrosive by inhalation. (based on components). Inhalation of corrosive fumes/gases may cause coughing, choking, headache, dizziness, and weakness for several hours. Pulmonary edema may occur with tightness in the chest, shortness of breath, bluish skin, decreased blood pressure, and increased heart rate. Inhaled corrosive substances can lead to a toxic edema of the lungs. Pulmonary edema can be fatal.

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye damage. (based on components). Corrosive to the eyes and may cause severe damage including blindness. May cause irreversible damage to eyes.

Skin contact Specific test data for the substance or mixture is not available. Corrosive. (based on

components). Causes burns.

Ingestion Specific test data for the substance or mixture is not available. Causes burns. (based on components). Ingestion causes burns of the upper digestive and respiratory tracts. May cause severe burning pain in the mouth and stomach with vomiting and diarrhea of dark blood. Blood pressure may decrease. Brownish or yellowish stains may be seen around the mouth. Swelling of the throat may cause shortness of breath and choking. May cause lung damage if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. Burning. May cause blindness. Coughing and/ or wheezing.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	13,428.60 mg/kg
ATEmix (dermal)	71,428.60 mg/kg
ATEmix (inhalation-gas)	5,714,285.70 ppm
ATEmix (inhalation-vapor)	62.10 mg/l
ATEmix (inhalation-dust/mist)	14.30 mg/l

3.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
3.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
3.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propane 74-98-6	-	-	> 800000 ppm (Rat) 15 min
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Tetrasodium ethylenediamine tetraacetate 64-02-8	= 1658 mg/kg (Rat)	-	-
Acetaldehyde 75-07-0	= 660 mg/kg (Rat)	= 3540 mg/kg (Rabbit)	= 13000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes severe skin burns and eye damage.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye damage. Causes burns.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA

Ethylene Glycol Monobutyl Ether 111-76-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-
Acetaldehyde 75-07-0	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans Group 2B - Possibly carcinogenic to humans	Reasonably Anticipated To Be A Human Carcinogen	Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylene Glycol Monobutyl Ether 111-76-2	-	LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	-	EC50: >1000mg/L (48h, Daphnia magna)
Tetrasodium ethylenediamine tetraacetate 64-02-8	-	LC50: =41mg/L (96h, Lepomis macrochirus) LC50: =59.8mg/L (96h, Pimephales promelas)	-	-
Acetaldehyde 75-07-0	-	LC50: 28.0 - 34.0mg/L (96h, Pimephales promelas) LC50: =53mg/L (96h, Lepomis macrochirus) LC50: 1.8 - 2.4mg/L (96h, Oncorhynchus mykiss) LC50: 39.8 - 46.8mg/L (96h, Pimephales promelas)	EC50 = 280.6 mg/L 15 min EC50 = 280.6 mg/L 25 min EC50 = 280.6 mg/L 5 min	EC50: 3.64 - 6.15mg/L (48h, Daphnia magna) EC50: =48.3mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Propane 74-98-6	1.09
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
Tetrasodium ethylenediamine tetraacetate 64-02-8	472- 500 mg/l

Acetaldehyde 75-07-0	0.63

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

California waste information This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information

NOTE: This information is not intended to convey all specific regulatory information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

DOT

UN number or ID number UN1950
Proper shipping name Aerosols, flammable Limited Quantity (LQ)
Transport hazard class(es) 2.1
Subsidiary hazard class 3

IATA

UN number or ID number UN1950
UN proper shipping name AEROSOLS, flammable, containing substances in Class 8, packing group I
Transport hazard class(es) 2.1
Subsidiary hazard class 3

UN number or ID number UN1950
UN proper shipping name AEROSOLS, flammable, containing substances in Class 8, packing group I
Transport hazard class(es) 2.1
Subsidiary hazard class 3

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing Chemicals Inventory
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	1.0
Acetaldehyde - 75-07-0	0.1

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Acetaldehyde 75-07-0	1000 lb	-	-	X

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Acetaldehyde	1000 lb /	-	RQ 1000 lb final RQ

75-07-0	kg (final RQ)		RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

NonHazardous

Chemical name	California Proposition 65
Acetaldehyde - 75-07-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Propane 74-98-6	X	X	X
Acetaldehyde 75-07-0	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA **Health hazards** 2 **Flammability** 3 **Instability** 0 **Special hazards** -

HMIS **Health hazards** 2 **Flammability** 3 **Physical hazards** 0 **Personal protection** X

Chronic Hazard Star Legend ** = Chronic Health Hazard*

Revision Date 18-Aug-2025

Revision Note No information available.

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However,Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of theinformation. User is responsible for evaluating whether such information or this product is fit for a particular purposeand suitable for a particular use or application. The information in this data sheet may not be valid if this product is usedin combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims anyliability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of thisproduct. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.